

FULL STAINLESS STEEL REPAIR CLAMP- PN10/16

From DN50 to DN300

Repairing clamp standard: comply with EN545

Coating standard: EN30677

Test standard: EN12266-1

Working pressure and Temperature size

OD50 to OD300, Working pressure PN10/PN16

Temperature from -10°C to 120°C for EPDM gasket

Temperature from -10 °C to 82°C for NBR gasket.

Suitable for potable water, neutral liquids and sewage

WRAS approved is available upon request.



Material specification

SR. NO.	Name	Material
1	Bolt	Stainless Steel
2	Nut	Stainless Steel
3	Washer	Stainless Steel
4	Locking Plate	Stainless Steel
5	Lugs	Stainless Steel
6	Junction Plate	Stainless Steel
7	Band	Stainless Steel
8	Sealing rubber	EPDM

SIZE	OD RANGE	LENGTH	BOLTS	WORKING PRESSURE
DN50	60-67	150/200	M16x180	PN10/16
DN80	88-98	50/200/300	M16x180	PN10/16
DN80	95-105	50/200/300	M16x180	PN10/16
DN100	108-118	50/200/300	M16x180	PN10
DN100	115-128	150/200/300	M16x180	PN10
DN150	158-172	200/300	M16x180	PN10
DN150	168-182	200/300	M16x180	PN10
DN200	217-229	200/300	M16x180	PN10
DN200	225-240	200/300	M16x180	PN10
DN250	243-260	200/300/450	M16x180	PN6/10
DN250	270-288	200/300/450	M16x180	PN6/10
DN300	313-336	200/300/450	M16x180	PN6/10
DN300	340-360	200/300/450	M16x180	PN6/10