

QUICK FLANGE ADAPTOR FOR PVC/HDPE PIPES PN10/PN16

From DN40 to DN400

Flange adaptor standard: comply with EN545

Coating standard:EN30677

Test standard: EN12266-1

Working pressure and Temperature size

OD40 to OD400, Working pressure PN10/PN16

Temperature from -10°C to 120°C for EPDM gasket

Temperature from -10 °C to 82°Cfor NBR gasket.

Suitable for potable water, neutral liquids and sewage
WRAS approved is available upon request.



Material specification

SR. NO.	Name	Material
1	Flange Body	Ductile iron
3	Ring	Brass
4	Gasket	EPDM

Size	Pipe OD	A	B	E	Weight	
					PVC	HDPE
DN40	50	166	118	55	1,74	1,79
DN50/65	63	184	156	68	1,84	1,9
DN60/65	63	184	156	68	1,72	1,78
DN60/DN65	75	185	139	80	1,89	1,96
DN80	75	201	161	80	2,46	2,54
DN80	90	196	151	96	2,46	2,57
DN100	110	220	181	113	3,09	3,24
DN125	125	254	211	131	4,14	4,46
DN125	140	254	212	140	4,32	4,83
DN150	160	283	244	165	5,45	6,07
DN200	200	338	297	206	6,25	7,14
DN200	225	338	299	231	7,18	8,11
DN250	250	402	360	257	9,73	10,93
DN300	315	454	412	321	14	15,44
DN400	400	570	529	410	21,8	23,54