

SADDLE FOR PVC/HDPE PIPES PN10/PN16

From DN50 to DN300

Saddle standard: comply with EN545

Coating standard: EN30677

Test standard: EN12266-1

Working pressure and Temperature size

OD50 to OD300, Working pressure PN10/PN16

Temperature from -10°C to 120°C for EPDM gasket

Temperature from -10 °C to 82°C for NBR gasket.

Suitable for potable water, neutral liquids and sewage
WRAS approved is available upon request.



Material specification

SR. NO.	Name	Material
1	Body	Ductile Iron
2	Gasket	EPDM
3	Bolts	SS304
4	Washer	SS304

PVC/PE PIPE OD(DE)	OUTLET THREAD SIZE	A	H	L	OD	BOLT SIZE
50	3/4"- 1 1/4"	85	50	81	117	M10X35
63	3/4"- 2"	95	53,5	91.2	133	M10X35
75	3/4"- 2"	110	61,5	102	147	M10X35
90	3/4"- 2"	127,5	71	100.5	157	M10X35
110	3/4"- 2"	147	82	102	179	M10X35
125	3/4"- 2"	166	93,4	111	201	M12X35
140	3/4"- 2"	173	94	110	216	M12X35
160	3/4"- 2"	197,5	106	126	237	M12X35
200	3/4"- 2"	244	129	143	191	M14X35
250	3/4"- 2"	296.5	155	145	343	M14X35
315	3/4"- 2"	319	18	145	408	M14X35