

UNIVERSAL DCI SADDLE WITH STAINLESS STEEL STRAP FLANGE OUTLET -PN10/PN16

From DN50 to DN500

Saddle standard: comply with EN545

Coating standard:EN30677

Test standard: EN12266-1

Working pressure and Temperature size

OD50 to OD500, Working pressure PN10/PN16

Temperature from -10°C to 120°C for EPDM gasket

Temperature from -10 °C to 82°Cfor NBR gasket.

Suitable for potable water, neutral liquids and sewage
WRAS approved is available upon request.



Material specification

SR. NO.	Name	Material
1	Body	Ductile Iron
2	Gasket	EPDM
3	Band	Stainless Steel

DN	OD	DN	øD		H	N-M
			PN10	PN16		
50	48-62	50	165	165	140	4-M12
65	57-78	50	165	165	150	4-M12
80	75-98	50	165	165	155	4-M12
80	75-98	65	185	185	155	4-M12
100	108-133	50	165	165	165	4-M12
100	108-133	65	185	185	165	4-M12
100	108-133	80	200	200	170	4-M12
125	122-146	50	165	165	180	4-M12
125	122-146	65	185	185	180	4-M12
125	122-146	80	200	200	185	4-M12
125	122-146	100	220	220	195	4-M12
150	158-177	50	165	165	190	4-M12
150	158-177	65	185	185	190	4-M12
150	158-177	80	200	200	200	4-M12
150	158-177	100	220	220	205	4-M12
200	206-236	80	200	200	225	4-M12
200	206-235	100	220	220	230	4-M12
200	206-235	150	285	285	245	6-M12
250	248-274	80	200	200	265	4-M12
250	248-274	100	220	220	270	4-M12
250	248-274	150	285	285	280	6-M12
250	248-274	200	340	340	290	6-M12
300	313-338	80	200	200	295	4-M16
300	313-338	100	220	220	300	4-M16
300	313-338	150	285	285	310	6-M16
300	313-338	200	340	340	320	6-M16
300	313-338	250	395	405	330	8-M16
500	508-532	100	220	220	405	4-M16