

UNIVERSAL DCI SADDLE WITH STAINLESS STEEL STRAP ,THREAD OUTLET -PN10/PN16

From DN50 to DN400

Saddle standard: comply with EN545

Coating standard:EN30677

Test standard: EN12266-1

Working pressure and Temperature size

OD50 to OD400, Working pressure PN10/PN16

Temperature from -10°C to 120°C for EPDM gasket

Temperature from -10 °C to 82°Cfor NBR gasket.

Suitable for potable water, neutral liquids and sewage

WRAS approved is available upon request.



Material specification

SR. NO.	Name	Material
1	Body	Ductile Iron
2	Gasket	EPDM
3	Band	Stainless Steel

Size	Band Thickness	Bolts length	Bolts thread length
54-64	1.5	M12X120	100
60-77	1.5	M12X120	100
77-95	1.5	M12X120	100
98-119	1.5	M12X120	100
102-122	1.5	M12X120	100
120-150	1.5	M12X150	130
125-125	1.5	M12X120	100
139-160	1.5	M12X120	100
150-180	1.5	M12X150	130
151-171	1.5	M12X120	100
160-185	1.5	M12X120	100
170-195	1.5	M12X120	100
173-198	1.5	M12X120	100
195-220	1.5	M12X120	100
200-230	1.5	M12X150	130
223-248	1.5	M12X120	100
230-250	1.5	M12X120	100
250-280	1.5	M12X150	130
285-315	1.5	M12X150	130
315-340	1.5	M12X120	100
320-345	1.5	M12X120	100
330-355	1.5	M12X120	100
355-380	1.5	M12X120	100
385-400	1.5	M12X120	100
400-425	1.5	M12X120	100
410-435	1.5	M12X120	100